

https://www.engineertools-jp.com/







HEAD OFFICE •

8-9, HIGASHI IMAZATO 2-CHOME, HIGASHINARIKU, OSAKA 537-0011, JAPAN TEL:06-6974-0028 FAX:06-6974-5661







Screw Removal Pliers Series




Socket Screw Extractor Series





Phillips Screw Extractor Series




Rust Remover















Plumbing Work

Necessary functions added for plumbing and piping works

Ideal for working in secluded places, and also for vinyl coated pipe works



Φ3~9.5

Auto Mechanic

The vice function allows the screw to be locked strongly



More big, more powerful!

PZ-68 NEW

PZ-64 · 65

For deep places

PZ-66





Φ3~9.5


Φ3~9.5

Φ3~9.5

Small type for easy handling and large type that is easy to apply force



Φ3~5.5



















· Tapered and slender head is ideal for working in a confined area

· Grip super-thin screw heads tightly!





Patented

















Comes with a pliers mask for neat storage (PZM-77)

(PZM-77P)



Your "Go-To" tool to tackle many daily challenges!


















Screw Removal Pliers GT (PZ-58)



· Spring loaded for fatigue-free work









Related Products






Dome head

Screw Eater (PZ-22)








T-shaped handles









- · Just grip and turn!! High leverage structure makes it easy to grip
- · Inter-meshed Side Teeth -- Enough force to grip ultra-thin plates as tightly as thick materials when the jaws are closed









Screw Removal Pliers (PZ-55)

• The basic Screw Removal Pliers: powerful and simple!







Item No.	Size	Tip hardness (HRC)	Applicable screw head size (mm)	Cutting capacity (mm)	Weight (g)	Material
PZ-77	W182xH50xD15			Copper Wire Φ4.0	183	
PZ-77P	W182xH50xD15	10.0	Ф3~9.5	Steel Wire Φ3.2	183	Body:Carbon Steel
PZ-58	W160xH54xD15	60±2	Ф3~9.5	Copper Wire Φ3.2 Steel Wire Φ2.6	130	Handles:TPR
PZ-22	W175xH52xD15			-	165	(Only PZ-55:PVC)
PZ-55	W150xH53xD11	56±2	Ф3~8	-	125	
PZM-77	-	-	*	-	×	
PZM-77P	2	9	-	=	-	TPR
PZM-58	-	-	-	*	(#)	

Electronic Work

Screw Removal Pliers m2 (PZ-57)



Convenient for working on electronic devices Small-sized 120mm body with ESD-safe handles

- · Ideal for removing small stripped or special screws
- · ESD-Safe TPR handles
- · Grip end with strap hole
- · Used for laptops, mother boards, prototype electronics, mobile phones, game consoles, RC toys, drones, character figures and other electronic appliances







Screw Removal Pliers Z (PZ-60)



T-shaped





Alligator-like tough gripping needle nose with screw removing jaws

- · Long nose pliers with non-slip gripping inter-meshed side teeth
- · Screw removal with vertical serrations at the tips just grip & turn!!
- · Durable comfort grips made of TPR
- · Side cutter for copper wires















Black Finish

Screw Removal Pliers JS(PZ-32)













Multi-purpose extraction tool for stubborn fasteners... Black finish!

- · Vertical serrations grip the screw head without slipping
- · Inter-meshed side teeth make it possible to hold very thin boards firmly
- · Black oxide coating to increase rust-resistance!



Related Products





Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size (mm)	Cutting capacity (mm)	Weight (g)	Material
PZ-57	W120xH52xD11	56±2	Φ2~3.5	-	100	D C C
PZ-60	W193xH57xD15		Φ2~5.5	Copper Wire Φ3.2	180	Body:Carbon Steel
PZ-32	W160xH55xD16	60±2	Φ3~9.5	Steel Wire Φ2.6	125	Handles:TPR
PZM-30		-	-	-	-	TPR

Maintenance

Screw Removal Pliers RX (PZ-59)













8-inches heavy-duty screw extracting tool, the multi-purpose gripping pliers The patented vertically-serrated jaws can bite a damaged, broken or rusted screw head with no slip!

- · Much faster than a fluted screw extractor bit and simpler than vise grip pliers
- · Ideal for professionals, auto mechanics, builders, etc
- · Inter-meshed side teeth make it possible to hold very thin boards firmly



Screw Removal Pliers CP (PZ-54)



Dome head





Slip-joint Screw Removal Pliers: 2-way opening jaws!

- · Unique and vertically-serrated jaws grip a stripped screw head securely without slipping
- · Much faster than a fluted screw extractor and simpler than vise grip pliers
- · Side cutter for steel wires. (dia. 2mm max.)
- · Side jaws ideal for holding a round pipe, hexagonal nut, etc



















Item No.	Size	Tip hardness (HRC)	Applicable screw head size (mm)	Cutting capacity (mm)	Weight (g)	Material
PZ-59	W204xH53xD19	60±2	Ф3~12	Copper Wire Φ3.5 Steel Wire Φ3.2	295	Body:Carbon Steel Handles:TPR
PZ-54	W175xH48xD14	00±2	Φ3~9.5	Steel Wire Φ2.0	155	Body:Carbon Steel Handles:PVC

Electrical Work

Screw Removal Pliers VAX (PZ-75) NEW

- · Grip super-thin screw heads tightly!
- · Cuts PVC insulated 3-core cables easily with one hand
- · A must for electricians!
















Dome head



Vertical serrations for screw removal

Screw Removal Pliers VA (PZ-79)

· Crimper for bare terminals (AWG16~12)

· Cross-hatched jaws to hold thin plates, cable ties and other parts tightly without slipping







Cross-hatch

· Unique screw removal jaws must for electricians

Screw Removal Pliers EL (PZ-78)







Dome head

























Strap hole

Crimper for

bare terminals 1.25~3.5mm²

	Item No.	Size	Tip hardness	Applicable screw head size (mm)	Cutting (Blade length	Weight (g)	Material
NEW	PZ-75	W205×H53×D14		Ф3~9.5		Steel Wire Φ2.5	20	297	Body:Carbon Steel
	PZ-79	W215×H52×D27	60±2	VVF2.6×3C		20	340	Handles:TPR	
	PZ-78	W225×H54×D27		Ф3~12		Steel Wire Φ3.2	21	350	(Only PZ-79:PVC)

Plumbing Work

Screw Removal Pliers WP-3 (PZ-82) NEW

- · Unique screw removal jaws must for plumbers & mechanics
- · 245mm long body with high leverage and wide opening jaws (max. 50mm)
- · Quick adjustment of opening jaws

Screw head size

φ3~9.5 mm

- · Holds round bars, square bars, hex. nuts, sheet metals, etc.
- Vertical serrations for removing stripped or rusty screws








Dome head RoHS2

Pipe Φ5~50mm Hex. nut 5~47mm

Quick Adjust Grooved Joint







Self-locking function

No need to adjust the jaws opening, just clamp it to lock!





Screw Removal Pliers VP-4 (PZ-67)







Screw Removal Pliers VP-5 (PZ-68) NEW























Clamping force adjustment



Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size (mm)	Weight (g)	Material
PZ-67	W175×H52×D18	57±3	+2 05	265	Dadiu Chuana Malukalanina
W PZ-68	W220×H64×D20	5/±3	Φ3~9.5	550	Body:Chrome Molybdenum

Screw Removal Pliers VP-1 · 2 (PZ-64 · 65)

Hold the screw head and lock it up to twist!!

· Quick release mechanism: just open the handles to unlock











Can be retightened with a hex key wrench (3mm)









Can be retightened with a hex key wrench (4mm)

Screw Removal Pliers VP-3 (PZ-66)

· Slender nose type















Can be retightened with a hex key wrench (3mm)









Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size (mm)	Cutting capacity (mm)	Weight (g)	Material
PZ-64	W150×H55×D18			Copper Wire Φ1.6	205	
PZ-65	W190×H70×D25	57±3	Φ3~9.5	Copper Wire Φ2.3	400	Body:Chrome Molybdenum Handles:TPR
PZ-66	W150×H55×D18			-	210	Hallules, IFN

Socket Screw Extractor Series



Remove stripped hex socket screws without hammering!








How to Choose


Short Type

[DBZ-310~350]



18mm Bits








Middle Type

[DBZ-410~450]



65mm Bits









Long Type

[DBZ-62~65]







15 Page

13 Page





Socket Type

[DWZ-05~10]



29mm Bits

Square drive type allen bolt extractors



Select by across flats size

Acro	ss Flats Size	но.89	H1.5	H2	H2.5	нз	Н4	Н5	Н6	Н8	H10
Short		310	315	320	325	330	340	350	-	-	-
Middle	DBZ-	410	415	420	425	430	440	450		+	-
Long		-	*	62	63	63	64	65		-	-
Socket	DWZ-	8	-	-	3	-	- 4	05	06	08	10



Select by screw size

Screw size	Hex socket screw	Button	Flat head	Hex socket set screw	
M1.0	DBZ-310 / 410	-	•	-	
M1.6	DBZ-315 / 415	-	-	-	
M2.0	DBZ-315 / 415	-	-	DBZ-310 / 410	
M2.5	DBZ-320 / 420 / 62	DBZ-315 / 415	DBZ-315 / 415		
M3.0	DBZ-325 / 425 / 63	DBZ-320 / 420 / 62	DBZ-320 / 420 / 62	DBZ-315 / 415	
M4.0	DBZ-330 / 430 / 63 DBZ-325 / 425 / 63		DBZ-325 / 425 / 63	DBZ-320 / 420 / 62	
M5.0	DBZ-340 / 440 / 64		DBZ-330 / 430 / 63	DBZ-325 / 425	
M6.0	DBZ-350 / 450 / 65 , DWZ-05	DBZ-340 / 440 / 64	DBZ-340 / 440 / 64	DBZ-330 / 430	
M8.0	DWZ-06	DBZ-350 / 450 / 65 , DWZ-05	DBZ-350 / 450 / 65 , DWZ-05	DBZ-340 / 440	
M10	DWZ-08	DWZ-06	DWZ-06	DBZ-350 / 450 / 65 , DWZ-05	
M12	DWZ-10	DWZ-08	DWZ-08	DWZ-06	
M14	-	-	DW7 40	-	
M16	-	DWZ-10	DWZ-10	DWZ-08	
M20	-	-	2	DWZ-10	


Application to Torx, Phillips, etc. Phillips





Select the appropriate size for the pilot hole





Drill a pilot hole in the center of screw head.

Apply the tip of the extractor and turn it counterclockwise.

Compatible screw

	Remove stripped hex socket screws without hammering						Application to Phillips,Torx			
Item No.	Across	Cap bolt	Hexagon socket		Hex socket	Diameter	Phillips	Torx	Max. limit	
	flats 🔾	Cap boil	Button	Flat head	set screw	(mm)	riiiips	TOTX	of size *1	
DBZ-310 / 410	H0.89	M1		-	M2	Ф 1.0	M1.6	T3,T4	M2	
DBZ-315 / 415	H1.5	M1.6,M2	M2.5	M2.5	M3	Ф 1.5	M2	T5,T6	M2.6	
DBZ-320 / 420 / 62	H2	M2.5	M3	M3	M4	Ф 2.0	M2.6	T7,T8	МЗ	
DBZ-325 / 425 / 63	H2.5	M3	M4	M4	M5 *2	Φ 2.5	M3	T10	M4	
DBZ-330 / 430 / 63	H3	M4	M5	M5	M6 *2	Ф 3.0	M4 *2	T15 *2	M5	
DBZ-340 / 440 / 64	H4	M5	M6	M6	M8 *2	Φ 4.0	M5	T20,T25	M6	
DBZ-350 / 450 / 65 , DWZ-05	H5	M6	M8	M8	M10	Ф 5.0	M6	T27,T30	M8	
DWZ-06	H6	M8	M10	M10	M12	Φ 6.0	M8	T40	M10	
DWZ-08	H8	M10	M12	M12	M16	Ф 8.0	M10	T45, T50	M12	
DWZ-10	H10	M12	M16	M14,M16	M20	Ф10.0	=	T55	M16	

- *1 Use of screws larger than the maximum size limit may result in damage. Excluding set screws.
- *2 Excluding DBZ-63, DBZ-64





For more information about tool selection and actual working methods, please check here.

▼ Watch the case study blog!















Socket Screw Extractor - Short Bits - (DBZ-310~350)

· Super-short (18mm) Socket screw extractors, ideal for working in narrow spaces.

Short Type


















Size / Compatible screw

Item No.	Across flats(mm)	Cap	Hex socket button& flat head	# 2 Hex socket set screw
DBZ-310	0.89 *1	M1	-	M2
DBZ-315	1.5	M1.6 / M2	M2.5	M3
DBZ-320	2	M 2.5	M3	M4
DBZ-325	2.5	МЗ	M4	M5
DBZ-330	3	M4	M5	M6
DBZ-340	4	M5	M6	M8
DBZ-350	5	M6	M8	M10



Size	(mm)	Weight		
Α	В	(g)		
5	Ø1.4	2.8		
6	Ø2.2	2.9		
6	Ø3.0	3.1		
6	Ø3.9	3.4		
6	Ø4.6	3.6		
6	Ø5.5	4.0		
-	_	4.3		
	A 5 6 6 6 6	5 Ø1.4 6 Ø2.2 6 Ø3.0 6 Ø3.9 6 Ø4.6 6 Ø5.5		

Socket Extractor Short Set (DBZ-301)

NEW



[Contents] DBZ-310 DBZ-315 DBZ-320 DBZ-325 DBZ-330 DBZ-340 DBZ-350

Socket Extractor Short Set (DBZ-302)

NEW



[Contents] DBZ-310 DBZ-315 DBZ-320 DBZ-325

Socket Extractor Short Set (DBZ-303)



[Contents] DBZ-325 DBZ-330 DBZ-340 DBZ-350

Mini Offset Ratchet with Socket Extractor Set (DZ-273)



Mini Offset Ratchet with Socket Extractor Set (DZ-275)



Mini Offset Ratchet with Socket Extractor Set (DZ-276)



[Contents] DR-27 DBZ-303

6.35 RoHS2

[Contents]

DR-27

DBZ-302

Mini Offset Ratchet (DR-27)

Super-thin head for narrow spaces

·Standard bits: (+) #2 & (-) 6mm





Middle Series

Socket Screw Extractor - Middle Bits - (DBZ-410~450)

· 65mm long Socket Screw Extractors

· Ideal for working in limited spaces

Middle Type








Size / Compatible screw

Item No.	Across flats(mm)	Cap bolt	Hex socket button& flat Head	* Hex socke set screy
DBZ-410	0.89 *1	M1	-	M2
DBZ-415	1.5	M1.6 / M2	M2.5	M3
DBZ-420	2	M 2.5	мз	M4
DBZ-425	2.5	M3	M4	M5
DBZ-430	3	M4	M5	M6
DBZ-440	4	M5	M6	M8
DBZ-450	5	M6	M8	M10



	Size	Weight	
Item No.	Α	В	(g)
DBZ-410	10	Ø1.4	11.5
DBZ-415	15	Ø2.2	11.2
DBZ-420	15	Ø3.0	11.4
DBZ-425		Ø3.9	12.6
DBZ-430	-	Ø4.6	13.5
DBZ-440		Ø5.5	14.6
DBZ-450	-	-	16.2

Socket Extractor Middle Set (DBZ-401)

NEW



[Contents] DBZ-410 DBZ-415 DBZ-420 DBZ-425 DBZ-430 DBZ-440 DBZ-450

Socket Extractor Middle Set (DBZ-402)

NEW



[Contents] DBZ-410 DBZ-415 DBZ-420 DBZ-425

Socket Extractor Middle Set (DBZ-403)

NEW



[Contents] DBZ-425 DBZ-430 DBZ-440 DBZ-450

Socket Screw Extractor Set with Mini Handle (DZ-84)



[Contents] DZ-80 DBZ-401

Socket Screw Extractor Set with Mini Handle (DZ-85)



[Contents] DZ-80 DBZ-402

Socket Screw Extractor Set with Mini Handle (DZ-86)



[Contents] DZ-80 DBZ-403

Mini Handle (DZ-80) Handle only NEW

Compact body with excellent portability and operability

· Rotary head for precision work







[Actual size]

14

(6.35) (C)

Long Series



	OI	9	99			mm) Item No.	Size (mm)	Weight (g)
Item No.	Across	Cap	Hex socket	*	25	DBZ-62		25
item No.	flats(mm)	bolt	button& flat head	Hex socket set screw		DBZ-63		27
DBZ-62	2	M2.5	МЗ	M4	105	DBZ-64	105	27
DBZ-63	2.5 ~ 3	M3 / M4	M4 / M5		k 105	DBZ-65		27
DBZ-64	4	M5	M6	-		DBZ-20		125
DBZ-65	5	M6	M8	M10				

(*) Do not use on stuck hex socket set screws.





Go-through Screwdriver (DZ-70) Handle only




[Contents] DZ-70

DBZ-20

100

- · Ergonomically designed comfort handle accepts 6.35mm driver bit (Bit length over 50mm recommended)
- · The handle is narrow in the middle to place fingers here for safety, and useful for quick tightening







Square Drive Series

Socket Screw Extractor -Square Drive type- (DWZ-05~10) NEW

- ·Removing hexagon socket (Allen) screws and hex. socket set screws that are broken by an Allen key. For hex. size 5-10mm (AF)
- ·Works with your own socket wrench handle (9.5mm sq. drive)


















ENGINEER

[Contents] DWZ-05, DWZ-06, DWZ-08, DWZ-10


		8	99	
Item No.	Across flats(mm)	Cap	Hex socket button& flat head	* Hex socket set screw
DWZ-05	5	M6	M8	M10
DWZ-06	6	M8	M10	M12
DWZ-08	8	M10	M12	M16
DW7-10	10	M12	M14/M16	Mag



Item No.	Size	Weight	
	A	В	(g)
DWZ-05	12.3	8	24
DWZ-06	13	9.6	26
DWZ-08	13.4	12.5	29
DWZ-10	14	15	33
DWZ-302	-		120

Combination of Socket Screw Extractors

Related products



Compatible tools	Mini Offset Ratchet (DR-27) Mini Ratchet Wrench (DR-37)	Extendable Ratchet Handle (DR-47) + Bit Adapter (DR-35)	Extension Bit Holder (DR-28) Universal Joint (DR-26)	Mini Handle (DZ-80) Go-Through Screwdriver (DZ-70)	Extension Bit Holder (DR-22 · 23 · 24) Universal Joint (DR-25)
Short Type (DBZ-310~350)	0	0	0	×	×
Middle Type (DBZ-410~450) 65 mm	Δ *	Δ *	Δ *	0	0
Long Type (DBZ-62~65)	Δ *	Δ *	Δ *	0	0


% It can be installed, but the bit may be damaged. Do not use for screws larger than M6.





Remove the stripped countersunk screw without hitting it with a hammer







Press & Twist type


DBZ-58

of the blade tip

Extractor Bit for "slightly damaged phillips screws" (DBZ-51·57·58)


- ·Elaborately crafted blades catch the stripped Phillips screw
- ·DBZ-51 for Phillips No.2 screw requires no hammer Simply press down on the screw & twist it out!!

DBZ-51










	T V
	0
Watch battery replacement	Glasses repair

DBZ-57



Strike & Turn type

Extractor Bit for "heavily damaged phillips screws" (DBZ-52)


·Strike the end with a hammer to stick the blade into the recess












Rapid removal! Designed for heavily-damaged hexagon socket screws

Strike & Turn type



into stripped hex. sockets







Item No.	Screw size	Weight (g)
DBZ-53	2.5~3mm	
DBZ-54	4mm	26
DBZ-56	5mm	

4-in-1 Rapid Screw Extractor Set (DBZ-22)



Bit holder included



Item No.	Case size (mm)	Weight (g)
DBZ-22	H165xW75xD10	125

Go-Through Screwdriver (DZ-76)



Go-Through Screwdriver 01 (DZ-71)

[Contents]

DZ-70

DBZ-51





Bit holder included

DZ-70 DBZ-58 DBZ-57 DBZ-51 DBZ-52

[Contents]








Phillips No.2

	Size (mm)				
Item No.	Shaft length (when inserted)	Shaft across flats	O.A. length	Handle diam.	Weigh (g)
DZ-76 DZ-71	73	6.35	194	38	250 170

4-in-1 Rapid Screw Extractor Set (DBZ-21)



[Contents] DBZ-57 DBZ-51 DBZ-52 DBZ-53



Item No.	Case size (mm)	Weigh (g)
DBZ-21	H165xW75xD10	125

6.35 RoHS2

6.35 PoHS2

Rapid Screw Extractor + Grip Set (DBZ-60G·50G)

The unique extracting tool, especially designed for removing damaged countersunk screws!

Bit holder included

- ·No power supply or drilling required
- · 2 bits, more possibilities · High-torque handle grip
- ·Shock-absorbable rubber sleeve included



[Contents] DBZ-50G DBZ-51 DBZ-52

	Item No.	(g)	Material
	DBZ-60G	131	■Bit:Carbon Steel ■Rubber:TPR ■Grip:ABS、PA
Grip only	DBZ-50G	83	■Grip: ABS、PA


Screw Removal Tool Kit By combining these, you can deal with various screw troubles














[Contents]

Item No.	Hex. size (across flats)
DBZ-62	2 mm
DBZ-63	2.5 ~ 3 mm
DBZ-64	4 mm
DBZ-65	5 mm









Works with stripped Phillips screws (No.0, No.1 & No.2 sizes)





Specifications		O Phi	O Hex socket screw	
		Slightly Damaged	Heavily Damaged	Hex socket screw
	DBZ-21	No.2 , No.1	No.2	Across flats 2.5~3 mm
	DB7-22	No.2 No.1 No.0	No.2	+

Go-through Screwdriver

Ergonomic design for powerful torque









transmitted well to the tip

(across flats 13mm)

Extension Bit Holder

Bit holders can also be used with an impact driver



DR-24





Can be used with a

Screwdriver Magnetizer

2 pcs. in a set Available in 3 colors

DR-19

DR-19P

DR-19Y

6.35 mm Hex.Shaft


retrieve screws

Magnetized bit can Holds even a stepped bit or torsion bit flexibly

Universal Joint







Slide the sleeve forward to swing the tip up to 15 degrees

Screw Extractor Tool Kit (DXZ-03~09)

If you're having trouble, start here! By combining these, you can deal various screw troubles.









7-in-1 set (DXZ-07)







Screw Removal Pliers (PZ-77)

8-in-1 set (DXZ-08)











Rust Remover (ZC-28E) Screws rusted and stuck? Try our Rust Remover to remove the rust off screws within seconds!

⚠ Do not reuse mechanical parts such as springs, chains, and bolts that are subject to strong forces, even after rust removal.

7-in-1 set (DXZ-09) NEW





Auto Locking Pliers (PZ-67)

CONTENTS



21




















(KSE-35)	
endineero	
	_

Versense Wales	Conten	ts									
Item No.	DZ-70	DBZ-20	DBZ-21	DBZ-22	DR-19	DR-23	DR-25	PZ-67	PZ-77	ZC-28E	KSE-35
DXZ-03	0	0	0								0
DXZ-04	0	0		0							0
DXZ-05	0	0	0		0	0	0				0
DXZ-06	0	0		0	0	0	0				0
DXZ-07	0	0		0	0	0	0		0		0
DXZ-08	0	0		0	0	0	0		0	0	0
DXZ-09	0	0		0	0	0	0	0			0

PDS-01

Screw Removal Pliers GT with Mask + Rapid Screw Extractor with 5 bits in a compact heavy duty case



Contents

Content	3		
PZ-58	Screw Removal Pliers GT	DBZ-52	Philips no. 2 (Strike & Turn type bit)
PZM-58	Mask for PZ-58	DBZ-53	Hex socket screw (Across flats: 2.5-3.0mr
DBZ-50B	Handle Grip for DBZ (Black)	DBZ-54	Hex socket screw (Across flats: 4.0mm)
DBZ-51	Philips no. 2 (Press & Twist type bit)	DBZ-56	Hex socket screw (Across flats: 5.0mm)
			Bit holder

PDS-02





PZ-58	Screw Removal Pliers GT	DBZ-52	Philips no. 2 (Strike & Turn type bit)
PZ-59	Screw Removal Pliers RX	DBZ-53	Hex socket screw (Across flats: 2.
PZ-60	Screw Removal Pliers Z	DBZ-54	Hex socket screw (Across flats: 4)
DBZ-50B	Handle Grip for DBZ (Black)	DBZ-56	Hex socket screw (Across flats: 5.
DBZ-51	Philips no. 2 (Press & Twist type bit)		Bit holder



PDS-03


Screw Removal Pliers PZ-33 with Mask cap + Rapid Screw Extractors and Socket Screw Extractors in a compact heavy-dutycase



PZ-33	Screw Removal Pliers DF	DBZ-62	Hex socket screw extractor (2.0mm)
PZM-30	Mask for PZ-33	DBZ-63	Hex socket screw extractor (2.5 - 3.0mm)
DBZ-50R	Handle Grip for DBZ (Red)	DBZ-64	Hex socket screw extractor (4.0mm)
DBZ-51	Philips no. 2 (Press & Twist type bit)	DBZ-65	Hex socket screw extractor (5.0mm)
			Bit holder

Rapid Screw Extractor Set(DBZ-01)


Rapid Screw Extractors + Hexagon Socket Screw Extractor of 10 bits in a compact heavy duty case




Contents

DBZ-50B	Handle Grip for DBZ (Black)	DBZ-52	Philips no. 2 (Strike & Turn type bit)
DBZ-57	Philips no. 1 (Press & Twist type bit)	DBZ-53	Hex socket screw (Across flats: 2.5-3.0mm)
DBZ-51	Philips no. 2 (Press & Twist type bit)	DBZ-54	Hex socket screw (Across flats: 4.0mm)
DBZ-63	Hex socket screw extractor (2.5 - 3.0mm)	DBZ-56	Hex socket screw (Across flats: 5.0mm)
DBZ-64	Hex socket screw extractor (4.0mm)	DR-94	Double-headed screwdriver bit (+ #2 / - 6mm
DBZ-65	Hex socket screw extractor (5.0mm)		














DR-19P

(Pink)

DR-19Y

(Yellow)





Item No.	Qty.	Shaft size (mm)			Weight (g/pc.)
DR-19 DR-19P DR-19Y	2pcs.	4~6.35	24	13	6.6

Mini Screwdriver Magnetizer (DR-29) NEW











The grooved housing holds the screw head securely. Common to DR-19.29

Item No.	Qty.	Shaft size (mm)	Size(mm) length width	

DR-29 3pcs. 4~6.35 16.2 13 4

Micro Screwdriver Magnetizer (DR-39) NEW



length width (g/pc.)

(mm)





Magnetized bit can retrieve screws!


Extension Bit Holder (DR-22-23-24)

Durable construction works with Go-through screwdrivers by hammering

- · Can also be used with an impact driver (except for DR-28)
- · Slim head ideal for working in a confined area
- For Standard Bit (DBZ-51~65 & 410~450 extractors attachable)








Item No.	Size (mm) A	Weight (g)
DR-22	100	40
DR-23	150	52
DR-24	190	60


Universal Joint (DR-25)

- · For screws in the corner or near the walls.
- · Unique tip structure prevents bit from coming off.









- 1) Do not use the Universal Joint in swing mode when it is attached to a power tool.
- 2) Use the low speed mode only.


 3) Make sure that the grooved shank is compatible with your power tool.

 4) The joint part heats up during the continuous use. Please work while cooling it with lubricating oil.

Item No.	Size (mm)	Weight (g)
DR-25	100	60




Extension Bit Holder (DR-28)



· Slim head ideal for working in a confined area








Idean No.	Size	MAGIE	
Item No.	(mm)	(g)	
DR-28		35	

Universal Joint (DR-26)

· The built-in magnet allows mounting of short bits without ball grooves.





Item No.	Size (mm)	Weight (g)
DR-26	100	53