



HEADS

OPTIONAL REPLACEABLE HEADS

RCK (Ring head)

HCK
(Hex drive head)

■ RCK ring heads

Unit : mm

Old Model	New Model	Size (W)				S	T	L ₁	φD ₁	φD ₂	Applicable torque wrench
230RCK	25RCK	7	8	9	10	18	8	45	10	16	60-250LCK, N6-N25LCK, 60-250SPCK, N6-N25SPCK, 250GCK, N25GCK, DTC-20REV, DTC-50REV, DTC-100REV, DTC-CN200REV, DTC-CN500REV, DTC-N10REV, DTC-PI-40REV, DTC-PI80REV
		11				21					
		12	13	14		31					
		17	19	22		32					
		24				32					
450RCK	50RCK	8	10			19	10	55	12	20	500LCK, N50LCK, 500SPCK, N50SPCK, 500GCK, N50GCK, DTC-500REV, DTC-N50REV, DTC-PI400REV, DLT-N50UC
		11	12	13	14	32					
		17	19	22		32					
900RCK	100RCK	12	13	14		25	13	65	15	23	1000LCK, N100LCK, 1000SPCK, N100SPCK, 1000, 1400GCK, N100, N140GCK, DTC-1000REV, DTC-N100REV, DTC-PI800REV, DLT-N100-UC
		17	19	21	22	34					
		24	27	30		42					
1800RCK	200RCK	17	19	22		35	15	80	18	27	2000LCK, N200LCK, 2000SPCK, N200SPCK, 2000GCK, N200GCK, DTC-2000REV, DTC-N200REV, DTC-PF100REV, DLT-N200-UC
		24	27	30		45					
		32	36	41		58					
2800RCK	280RCK	19	22	24		40	17	100	22	30	2800LCK, N280LCK, 2800SPCK, N280SPCK, DTC-3000REV, DTC-N300REV, DTC-PF200REV
		27	30	32		47					
		36	41			63					
4400RCK	440RCK	46				63	20	100	22	30	4400LCK, N440LCK, 4400SPCK, N440SPCK
		19	22	24		44					
		27	30	32		50					
		36	41			58					
		46	50			66					
7000RCK	700RCK	55	60			80	20	125	30	41	5600, 7000LCK, N560, N700LCK, DTC-5000REV, DTC-N500REV, DTC-PF400REV
		22	24			52					
		27	30	32		57					
		36				62					
		41				70					
10000RCK	1000RCK	46	50			80	25	130	34	45	8500, 10000LCK, N850, N1000LCK, DTC-10000REV, DTC-N1000REV
		55				80					
		60				80					
		27	30	32		60					
		36				65					
14000RCK	1500RCK	41				72	28	130	34	45	8500, 10000LCK, N850, N1000LCK, DTC-10000REV, DTC-N1000REV
		46				72					
		50				80					
		55				80					
		60				80					
2800RCK	280HCK	41				75	27	160	38	50	15000LCK, N1500LCK
		46				75					
		50				80					
		55				80					
		60				90					

■ HCK hex drive heads

Unit : mm

Old Model	New Model	Size (W)	L ₁	φD ₁	φD ₂	Size (H)	Applicable torque wrench
230HCK	25HCK	2.5	45	10	16	19	60-250LCK, N6-N25LCK, 60-250SPCK, N6-N25SPCK, 250GCK, N25GCK, DTC-20REV, DTC-50REV, DTC-100REV, DTC-CN200REV, DTC-CN500REV, DTC-N10REV, DTC-PI-40REV, DTC-PI80REV
		3				22	
		4				25	
		5				30	
		6				35	
450HCK	50HCK	8	55	12	20	40	500LCK, N50LCK, 500SPCK, N50SPCK, 500GCK, N50GCK, DTC-500REV, DTC-N50REV, DTC-PI400REV, DLT-N50UC
		10				45	
		4				27	
		5				30	
		6				35	
900HCK	100HCK	8	65	15	23	40	1000LCK, N100LCK, 1000SPCK, N100SPCK, 1000, 1400GCK, N100, N140GCK, DTC-1000REV, DTC-N100REV, DTC-PI800REV, DLT-N100-UC
		10				45	
		12				51	
		14				63	
		8				40	
1800HCK	200HCK	10	80	18	28	45	2000LCK, N200LCK, 2000SPCK, N200SPCK, 2000GCK, N200GCK, DTC-2000REV, DTC-N200REV, DTC-PF100REV, DLT-N200-UC
		12				51	
		14				63	
		17				72	
		12				51	
2800HCK	280HCK	14	100	22	30	63	2800LCK, N280LCK, 2800SPCK, N280SPCK, DTC-3000REV, DTC-N300REV, DTC-PF200REV
		17				71	
		19				80	
		12				51	
		14				63	

* is the new model that is applied from 1st January, 2016.