DTDK-REV DATA OUTPUT DIGITAL TORQUE DRIVER

Multi function data out put digital torque driver with OLED display.

FEATURES

Accuracy :±1% of indicated value +1 increment, over full range

: OLED Display

■ Measuring mode : ①Peak hold ②Peak to Peak ③Tracking Measuring direction CW / CCW changeover, provided with

: CW / CCW status display

: Lithium-ion rechargeable battery 18650 Power supply

100-240V battery charger

 Battery Life : Approx. 20 hours with fully charged

battery. (continuous operation)

Auto power-off : Approx. 30 minutes

: 1 to 10%. Automatic judgment for pre-set target torque Tolerance setting

Data input : 1000 data can be stored

STON. CHOOREY II	

Model	Range (Unit)	Increment	Weight (kg)	Accessory
				Standard bits
				Phillips SB type
DTDK-CN200REV	20~200 cN⋅m	0.1 cN · m	1	No.0, No.1
DTDK-CN500REV	50~500 cN⋅m	0.1 cN ⋅ m	1	No.1, No.2
DTDK-20REV	2~20 Kgf•cm	0.01 Kgf • cm	1	No.0, No.1
DTDK-50REV	5∼50 Kgf•cm	0.01 Kgf • cm	1	No.1, No.2

